

TIMKEN

The Timken Company
4500 Mt Pleasant St. NW
N. Canton, OH 44720
Phone: (234) 262-3000
E-Mail: CustomerCAD@timken.com • Web site: www.timken.com

Part Number CB-6S, Aurora Bearing CM-S & CB-S Series Male Rod Ends with Studs - General Purpose - Economy



- Body - Low carbon steel - protective coated for corrosion resistance.
- Ball - Alloy steel - heat treated - hard chrome plated.
- Stud - Low carbon steel - protective coated for corrosion resistance. Right hand threads are standard.
- Grease Fitting available for sizes -6 and up. Units are supplied without grease fittings. When a grease fitting is required, specify by adding suffix "Z" or "F". Ex.: CM-6SZ = Zerk Type Fitting CM-6SF = Flush Type Fitting.
- Optional grease fitting is supplied, standard, in **right hand** location (with stud facing away from you). Specify if **left hand** location is desired.

Key Dimensions




Part Number	CB-6S
Thread Type	Left Hand
Thread Configuration	Male
W - Ball Width	.500 in
H - Head Width	.359 in
A - Base to Center	1.938 in
D - Head Diameter	1.000 in
Ball Diameter	.719 in
C - Thread Length	1.250 in
L - Center to End of Stud	1.562 in
N - Stud Shank Length	.906 in
M - Stud Thread Length	.812 in
Thread Size	3/8-24
Thread Class	UNF-3A-LH
Thread Class Stud	UNF-2A
Hex Stud	.500 in
a - Misalignment Angle Total	45 °
Ultimate Radial Static Load Capacity	1,014 lbs
Approximate Brg. Weight	.15 lb
Lubrication Options	Zerk Fitting or Flush Fitting

**Grease Fitting
Location**

Right Hand or Left Hand

Note

For dimensional tolerances of listed features, see the PDF version of the catalog under the "View Product Catalogs" tab from the home page.



Component Materials

Body: Low carbon steel - protective coated for corrosion resistance.
 Ball: Alloy steel - heat treated - hard chrome plated.
 Stud: Low carbon steel - protective coated for corrosion resistance. Right hand thread.

Part No. : CB-6S	Description : Aurora Bearing CM-S & CB-S Series Male Rod Ends with Studs - General Purpose - Economy
Ultimate Radial Static Load Capacity : 1,014 lbs	Note : - Drawing not to Scale - Dimensions subject to change. - Above dimensions are nominal, see catalog charts for tolerances



The Timken Company

Address : 901 Aucutt Rd.

Montgomery, IL 60538

Tel. : 630.859.2030

Email : customerservice@aurorabearing.com

Web : www.aurorabearing.com